

## Fertilzer Spreading Bucket

The Ground-Effect Spreading Bucket range has been designed by IMS New Zealand to be strong, lightweight and to maximise the efficiency and distribution of product.

The **Ground-Effect Spreading Buckets** have a slide valve with interchangeable orifice plates of varying sizes, which determines the rate of application. The unique hopper design ensures complete evacuation. The engines have been chosen for their high power-to-weight ratios, and the spinner is designed to ensure a maximum swath width and even product spread.

**Ground-Effect Spreading Buckets** are suitable for application rates of up to 400kg/ha (360lbs/ac) and can be custom-made to suit the operator's requirements.

They are designed for either dry granular products or can be built for hydroseeding or wet applications. Ask us for help in selecting the right system for you





### Capacities

Part Number	Capacity (Liters)	Capacity (US Gallons)	Capacity (Cubic Feet)
GE200	200	53	7
GE300	300	79	10.6
GE350	350	92	12.4
GE400	400	106	14.1
GE560	560	148	19.8
GE650	650	172	22.9
GE750	750	198	26.5
GE950	950	251	33.5
GE1200	1200	316	40.6
GE1350	1350	355	45.9
GE1500	1500	396	53
GE1650	1650	436	58.3
GE2400	2400	634	84.7
GE2700	2700	713	95.3
Other volume sizes can be built according to your needs.			

## **Granular Variable Flow Control**

With the option of choosing variable control in this series of the Ground-Effect Spreading Bucket, the pilot can manually adjust the Variable Flow Control Valve using the remote speed control. This adjustment can be made while in flight.



### **Capacities**

Part Number	Capacity (Liters)	Capacity (US Gallons)	Capacity (Cubic Feet)
GE200	200	53	7
GE300	300	79	10.6
GE350	350	92	12.4
GE400	400	106	14.1
GE560	560	148	19.8
GE650	650	172	22.9
GE750	750	198	26.5
GE950	950	251	33.5
GE1200	1200	316	40.6
GE1350	1350	355	45.9
GE1500	1500	396	53
GE1650	1650	436	58.3
GE2400	2400	634	84.7
GE2700	2700	713	95.3

Other volume sizes can be built according to your needs.

#### The Variable Flow Control

**Valve** has been designed for the application of dry media. 1kg to 200kgs per hectare or 0.9lbs to 178lbs per acre.

Product flow rates can be adjusted during flight.

## Spreading Bucket Accessories

Ground-Effect Spreading Buckets can be specifically designed for various purposes, including pest and mosquito control.






#### **Hopper Lid**

**Hopper Lids** with robust zipped openings are available for the entire **Ground-Effect** range.

#### Spinner & Motor

A range of spinner and motor configurations are available to suit your specific application requirements. Our team will work with you to supply the optimum system for your needs.





### Bucket Mounted Air Compressor

Providing a compressed air supply to operate the Slide Valve ensures fast opening and closing movements.





### **Product Agitator**

Maximizes product flow to the spinner and reduces product bridging in the Hopper.



Agitator drive system. Rotates when Slide Valve is open.



# **Heavy Rate Applicator (HRA)**

The Heavy Rate Applicator is designed for applying bulk wet or dry products at rates exceeding 500kg per hectare (446lbs per acre).

The **Heavy Rate Applicator's** valve opening is pneumatic and is powered by a bucket-mounted air compressor. Adjusting the door opening position allows the operator to vary the application rate easily and quickly, without the need for any special tools.

Agitator systems are also available for the **Heavy Rate Applicator**, which minimizes the risk of dry product bridging or hanging up in the bucket.

These systems are available in a range of sizes and come complete with certified **Lifting Lines**, **Spreader Bar** suited to your helicopter, and wiring to the top of the **Lift Lines**.

Contact us for information on a system that best suits your application.

#### **Capacities**

Capacity (US Gallons)	Capacity (Liters)	Capacity (Cubic Feet)
106	400	14.1
119	450	15.9
132	500	17.6
145	550	19
158	600	21
171	650	23
184	700	24
250	950	33.5
277	1050	37
330	1250	44.1
356	1350	47.7
435	1650	58.2

Other volume sizes can be built according to your needs.







8 r6

## Concrete Skip

### For the cartage of concrete.

A full range of **Concrete Skips** are available to meet your specific needs, with various volumes and release configurations, including electric and manual operation.

These durable skips can be constructed from either aluminum or steel.





### **Capacities**

Capacity (US Gallons)	Capacity (Liters)	<b>Capacity</b> (Cubic Feet)
40	150	5.3
53	200	7
66	250	8.8
79	300	10.6
92	350	12.4
106	400	14.1
119	450	15.9
132	500	17.6
145	550	19
158	600	21
171	650	23
184	700	24
237	900	32
290	1100	39
286	1300	46
396	1500	53

Other volume sizes can be built according to your needs.



# **Gravel Skip**

### Designed for transportation of gravel products.

Clam shell door opening/closing either manual or electric over pneumatic.



#### Capacities

Capacity (US Gallons)	Capacity (Liters)	Capacity (Cubic Feet)
132	500	17.6
184	700	24
237	900	32
290	1100	39

Other volume sizes can be built according to your needs.



### Hydra-Loader

Looking for a fast and effective way to load your Ground-Effect Spreading Bucket, HRA or Gravel Skip? Consider our Hydra-Loader.

The **Ground-Effect Hydra-Loader** incorporates a digital load cell system to ensure precise bucket loading saving you time and ensuring effortless accuracy and consistency with each job.



**Conveyor Loader option** 



## Fire Lighter

The Ground-Effect Fire Lighter is manufactured from corrosion-resistant Stainless Steel to withstand the environment and products.

The user-friendly design includes a 150mm (6-inch) filler cap and a manual product agitator. Additionally, a variable speed controller, accessible during operation, controls the flow rate of the product, and the pump and igniter turn on and off simultaneously when switched at the pilot controls.



12

### **Long Lines**

The Ground-Effect Long Lines come in standard lengths of 50ft (15m), 100ft (30m), 150ft (45m), 200ft (60m), or the length can be customized for specific purpose.

These **Long Lines** are made from low-stretch Dynice Dux SK75 rope with a smooth polyurethane impregnation, which enhances abrasion resistance. These ropes offer a high strength-to-weight ratio.

The protective sheaths are constructed from durable and waterproof PVC with UV protective stitching. They are designed to incorporate electrical cables and pneumatic/hydraulic hoses as needed.





## **Swivels and Hooks**

#### **Manual and Remote Hooks**

We hold a range of remote hooks, which come complete with a full cage and wiring loom to match our swivels. We offer assistance and ongoing product support for required airworthiness inspections and overhauls. There are many manual hook combinations that may be suitable for your specific needs. Please get in contact to discuss further.

#### **Multi-Hook Carousels**

**Multi-Hook Carousels** are manufactured in 2-10 hook combinations. These multi-drop delivery systems are versatile and reliable, making the placement of multiple loads efficient and specific.

#### **Swivels**

We produce a range of high-quality swivels suitable for any type of helicopter, with an emphasis on reliability and smooth operation. Electrical services are available on Swivels, and they can be configured to suit any **Long Line**/ accessory configuration.





# Cargo Nets and Lifting Strops

Ground-Effect Cargo Nets can be manufactured to suit your needs. All Cargo Nets come with certification and a carry bag. Please contact our team for assistance.







SPREADING BUCKET

a product by IMS

#### **IMS New Zealand Limited**

**P.** +64 21 583 033 **E.** imssales@imsheli.com

FB. facebook.com/groundeffectspreadingbucket

IG. instagram.com/groundeffectspreadingbucket

LI. linkedin.com/company/ims-new-zealand



www.imsheli.com